

372 - SYNTHETIC CUTTING FLUID



Water Dilutable Cutting Fluid

Oil-free synthetic formula maintains integrity under high pressures for better and longer lasting lubrication and cooling without smoking. For use on ferrous and non-ferrous metals. Cools the tool and cutting surface and minimizes heat distortion. Reduces abrasive wear prolonging tool life and yielding quality finishes. Will not gum or clog coolant lines. Nitrate-free formula prevents freezing of chucks and collets. Water dilution ratios and applications: Heavy Duty: 1:10 for broaching, tapping, threading, and gear shaving; Medium Duty: 1:20 for cutting, drilling, reaming, milling, boring, turning, planning, shaping and sawing; Light Duty: 1:30 for form and surface grinding.

[372B SDS](#)

SKU: N/A | **Categories:** [Chemicals](#), [Cutting Fluids](#) |



VARIATIONS

Image	SKU	Price	Description	OPTIONS
	372-4X1		4 x 1 Gallon Case	
	372-5		2 x 2.5 Gallon Case	
	372-55		55 Gallon Drum	

GALLERY IMAGES



ADDITIONAL INFORMATION

OPTIONS

372-4X1: 4 x 1 Gallon Case, 372-5: 2 x 2.5 Gallon Case, 372-55: 55 Gallon Drum

