PROCOOL PC2 V/G COOLING SYSTEM



Specifications

• Factory set at 50 psi adjustable to 80 psi
• 3 gallon reservoir
• 115 or 230 VAC / 1 ph-50/60Hz
• 5.6 / 2.8 amp:60 Hz
• 12,000 BTU
• Dimensions: 18"L x 14"W x 9"H
• Net weight: 37 lbs / 17 kg
• Foam packed for UPS shipment

PCIIG: Rotary GEAR Pump

• 1.8 gpm at 50 psi
• Built in by-pass to tank
• Rebuildable Pump (Repair Kit Product No. P3001)

PCIIV: Rotary VANE Pump

1.7 gpm at 50 psi

System Features

• Plastic water tank eliminates coolant contamination due to electrolysis or chemical reactions.
• All units are plumbed with copper tubing and reinforced hose.
• New extended life pump features a direct drive power system reducing maintenance and vibration.
• No external plumbing is required because of closed loop water system.
• Self priming pump
• Easy change pump
• Strong rigid construction designed to support power unit.
• Compact design

Equipment	UP TO
M.I.G. guns	500 amps
T.I.G. torches	500 amps
RESISTANCE Welders	60 KVA

SKU: N/A | **Categories:** Machines, Water Recirculators |

GALLERY IMAGES

