



Safety Data Sheet

Dynaflux 366A SDS 07/18/2018

Product: 366 Solvent Degreaser (Aerosol)

Part 1: Product and Company Identification

Identification 366A

Trade Name: 366 Solvent Degreaser (Aerosol)

Product Use: Aerosol degreaser.

Manufacturers Name: Dynaflux, Inc.

241 Brown Farm Rd.

Cartersville, GA 30120 U.S.A.

Preparation Date: 08/13/2013

Emergency Telephone Number: For U.S.: 800-255-3924 International: 813-248-0585

Part 2: Hazard(s) IdentificationSignal Word: **DANGER****H223:** Flammable aerosol**H229:** Pressurized container may burst if heated**H361:** Suspected of damaging fertility or the unborn child.**Part 3: Composition / information on ingredients**

COMPONENTS	CAS NO.	% BY WEIGHT
Toluene	108-88-3	2-12%
Methanol	67-56-1	2-12%
Acetone	67-64-1	80-90%
Carbon Dioxide	124-38-9	2-12%

Part 3: Hazardous Identification

Emergency Overview: Product is extremely flammable. Pressurized container may rupture when exposed to heat or flame. Contact may cause skin and eye irritation. Mist may cause nose and throat irritation. Ingestion may cause nausea, vomiting, pain, upset stomach, and diarrhea.

Potential health effects: **Skin Contact:** This product may cause irritation to the skin. Prolonged or repeated contact with this product may dry and/or defat the skin. This product may be harmful if it is absorbed through the skin. **Eye Contact:** Liquid or vapors may irritate the eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Eye contact may lead to permanent damage if not treated promptly. **Ingestion:** This product is harmful if swallowed. Ingestion can cause gastrointestinal irritation, nausea, and diarrhea. **Target Organs:** Central Nervous System, lungs, skin, eyes. **Inhalation:** This product may cause dizziness, nausea, upper respiratory irritation, drowsiness, mental depression or narcosis, difficulty in breathing, irregular heart beats. See Section 8 for recommended exposure limits.

Part 4: First Aid Measures

Eye Contact: Flush with water for 15 minutes. Get medical attention. **GHS Category 2B**

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder before re-use. **GHS Category 3**

Inhalation: Move to fresh air. If normal breathing is not achieved get medical attention.

Ingestion: Do not induce vomiting. Get medical attention immediately. **GHS Category 2**

Part 5: Fire Fighting Measures

Extinguishing Media: Use dry chemical, carbon dioxide, or foam. Use water to cool fire-exposed containers and to protect personnel. Do not direct a solid stream of water or foam into hot, burning pools this may result in frothing and increase fire intensity. **Basic Fire Fighting Procedures:** Dangerous when exposed to heat or flame. This material can be ignited by flame or spark under normal atmospheric condition. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back. Pressurized Container: May rupture when exposed to heat or flame. Empty containers may retain product residue including Flammable or Explosive vapors. DO NOT cut, drill, grind, or weld near full, partially full, or empty product containers. **Dust Explosion Hazard:** None known. **Sensitivity To Mechanical Impact:** Container could potentially burst or be punctured upon mechanical impact, releasing flammable vapors. **Unusual Fire & Explosion Hazards:** During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. High temperatures can cause sealed containers to rupture due to a build up of internal pressures. Cool with water. **Fire Fighting Equipment/Instructions:** Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Flash Point: concentrate: > -20C

propellant: N/A

Flammability limits in air: 12.8 upper % by volume concentrate
N/A upper % by volume propellant

2.6 lower % by volume concentrate
N/A lower % by volume propellant

Part 6: Accidental Release Measures

Emergency Action: Evacuate the area promptly and keep upwind of the spilled material. Isolate the spill area to prevent people from entering. Wear appropriate protective equipment and clothing during clean-up. **Containment:** Stop discharge if safe to do so. Stop material from contaminating soil or from entering sewers or water streams. Cover spills with non-flammable absorbent and place in closed chemical waste containers

Part 7: Handling & Storage

Handling: Keep this product away from heat, sparks or open flame. Avoid getting this material into contact with your skin and eyes. Avoid breathing mists or aerosols of this product. Use this product with adequate ventilation. Do not reuse the empty container. **Storage:** Store in a cool, dry, well-ventilated area. Do not handle or store near an open flame, heat or other sources of ignition. Keep out of direct sunlight. Do not store above 120F (49 C). **Empty Container Precautions:** Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container.

Part 8: Exposure Controls / Personal Protection

Engineering Controls: Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product. **Eye Protection:** Wear goggles or safety glasses with side shields. **Skin and Body Protection:** Impervious gloves should be used when handling this product. Use of protective coveralls and long sleeves is recommended. **Respiratory Protection:** Use NIOSH approved respiratory protection. High airborne concentrations may necessitate the use of self-contained breathing apparatus (SCBA). **General:** Use good hygiene practices in handling this material. Continued

Exposure Limits: (PARTS PER MILLION)

Component(s)	TLV	OSHA-PEL	OSHA-STEL	SARA 313	Prop 65	VOC
Toluene	20ppm			X	X	X
Methanol	200ppm		250ppm			X
Acetone	500ppm	1000ppm	750ppm	X		
Carbon Dioxide	5000ppm	5000ppm	30000ppm			

Part 9: Physical & Chemical Properties**Solids:** N/A**PH:** N/A**Specific Gravity:** 0.7755**Physical State:** Liquid**%VOC:** 10%**Evaporation Rate:** >1 (butyl acetate=1)**Boiling Point:** N/A**Color:** Clear**Odor:** Characteristic**Part 10: Stability & Reactivity**

Hazardous polymerization will not occur. Condition to avoid: Keep away from sources of ignition. Avoid contact with strong oxidizers, reducers, acids, and alkalis. Stability: This product is stable under normal conditions.

Part 11: Toxicological Information**Toluene:** Oral LD50: 636 mg/kg (rat)Inhalation LC50: 49 gm/m³/4H

Dermal LD50: 14100 uL/kg (rabbit)

Methanol: Oral LD50: 6.2 g/kg (rat)

Inhalation LC50: >22500 ppm/8H (rat)

Dermal LD50: 15.89 g/kg (rabbit)

Acetone: Oral LD50: 5,800 mg/kg (rat)

Inhalation LC50: >16000 ppm/4H (rat)

Dermal LD50: >20,000 mg/kg (rabbit)

Carbon Dioxide: IDLH: 40000 ppm**Part 12: Ecological Information**

No information available

Part 13: Disposal Considerations

We make no guarantee of warranty of any kind that the use of and/or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Waste Disposal: Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations. Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes.

Part 14: Transportation Information

Ground Transportation: (Continental United States, Canada & Mexico): Consumer Commodity ORM-D

Ocean: UN 1950 Class 2.1, Limited Quantity

Air: We do NOT recommend this product to be shipped via air. It would need to be repacked by an authorized packing company and the DG would have to be completed by a licensed hazardous material shipping company.

Part 15: Regulatory Information

Toluene: TSCA Inventory

SARA 311/312: Acute Health Hazard
Chronic Health Hazard
Fire Hazard
CERCLA: Toluene (108-88-3) 1000 lbs.

Methanol: TSCA Inventory

SARA 311/312: Acute Health Hazard
Chronic Health Hazard
Fire Hazard

Acetone: TSCA Inventory

SARA 311/312: Acute Health Hazard
Fire Hazard
CERCLA: Acetone (67-64-1) 5000 lbs.

Carbon Dioxide: TSCA Inventory

SARA 311/312: Acute Health Hazard
Chronic Health Hazard

California Proposition 65 Statement:



WARNING: This product can expose you to Toluene and Methanol, chemicals known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65Warnings.ca.gov/product.

Part 16: Other Information

Dynaflux, Inc.
241 Brown Farm Rd.
Cartersville, GA 30120 U.S.A.
Completed by: Eugene Schaffstall

Continued

Disclaimer of Expressed and implied Warranties:

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date of the Safety Data sheet was prepared. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices as specified on the label copy.