

Safety Data Sheet Product: Dynaflux Skip Spat Anti-spatter (Aerosol)

Dynaflux 402A SDS 07/18/2018

Part 1: Product and Company Identification

Identification 402A Trade Name: Dynaflux Skip Spat (Aerosol) Product Use: High Temperature Water Based Anti-Spatter Manufacturers Name: Dynaflux, Inc. 241 Brown Farm Rd.

Cartersville, GA 30120 U.S.A.

Preparation Date: 08/13/2013 Emergency Telephone Number: For U.S.: 800-255-3924 International: 813-248-0585

Part 2: Hazard Identification



Signal Word: WARNING H229: Pressurized container: may burst if heated H302: Harmful to skin H313: May cause irritation to skin H320: Causes eye irritation H336: May cause drowsiness or dizziness

Emergency Overview: Product is non-flammable. Pressurized container may explode when exposed to heat or flame. Contact may cause skin and eye irritation. Mist may cause nose and throat irritation. Ingestion may cause nausea, vomiting, pain, upset stomach, and diarrhea.

Potential health effects: Skin Contact: This product may cause irritation to the skin. Prolonged or repeated contact with this product may dry and/or defat the skin. This product may be harmful if it is absorbed through the skin. **Eye Contact:** Liquid or vapors may irritate the eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Eye contact may lead to permanent damage if not treated promptly. **Ingestion:** This product is harmful if swallowed. Ingestion can cause gastrointestinal irritation, nausea, and diarrhea. **Target Organs:** Central Nervous System, lungs, skin, eyes. **Inhalation:** This product may cause dizziness, nausea, upper respiratory irritation, drowsiness, mental depression or narcosis, difficulty in breathing, irregular heartbeats. See Section 8 for recommended exposure limits

Part 3: Components / information on ingredients

COMPONENT(S)	CAS #	% by Weight	
Polyalkylene Glycol monobutyl ether	9003-11-6	<10%	
Nitrogen	7727-37-9	<5%	

Remaining components (Non-hazardous)not listed; trade secret Refer to Section 8 for recommendations.

Part 4: First Aid Measures

Skin: For skin contact, wash immediately with soap and water. If irritation persists, get medical attention. GHS Category: 3
Eye: Immediately flush with plenty of water for at least 15 minutes, holding eyelids open at all times. Get medical attention immediately. GHS Category: 2B Inhalation: Move person to non-contaminated air. If the affected person is not breathing, apply artificial respiration. Call a physician if symptoms develop or persist. Ingestion: If the material is swallowed, get immediate medical attention or advice. DO NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. GHS Category: 2

Part 5: Fire Fighting Measures

Extinguishing Media: Use dry chemical, carbon dioxide, or foam. Use water to cool fire-exposed containers and to protect personnel. Do not direct a solid stream of water or foam into hot, burning pools this may results in frothing and increase fire intensity. **Basic Fire Fighting Procedures:** Dangerous when exposed to heat or flame. Pressurized Container: May rupture when exposed to heat or flame. **Dust Explosion Hazard:** None known. **Sensitivity To Mechanical Impact:** Container could potentially burst or be punctured upon mechanical impact, releasing flammable vapors. **Unusual Fire & Explosion Hazards:** During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. High temperatures can cause sealed containers to rupture due to a buildup of internal pressures. Cool with water. **Fire Fighting Equipment/Instructions:** Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Flash Point: concentrate: N/Apropellant: N/AFlammability limits in air: N/A upper % by volume concentrate
N/A upper % by volume propellant

N/A lower % by volume concentrate N/A lower % by volume propellant

Part 6: Accidental Release Measures

Emergency Action: Evacuate the area promptly and keep upwind of the spilled material. Isolate the spill area to prevent people from entering. Wear appropriate protective equipment and clothing during clean-up. **Containment:** Stop discharge if safe to do so. Stop material from contaminating soil or from entering sewers or water streams. Cover spills with non-flammable absorbent and place in closed chemical waste containers.

Part 7: Handling & Storage

Handling: Keep this product away from heat, sparks or open flame. Avoid getting this material into contact with your skin and eyes. Avoid breathing mists or aerosols of this product. Use this product with adequate ventilation. Do not reuse the empty container. **Storage:** Store in a cool, dry, well-ventilated area. Do not handle or store near an open flame, heat or other sources of ignition. Keep out of direct sunlight. Do not store above 120F (49 C). **Empty Container Precautions:** Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container.

Part 8: Exposure Controls / Personal Protection

Engineering Controls: Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product. **Eye Protection:** Wear goggles or safety glasses with side shields. **Skin and Body Protection:** Impervious gloves should be used when handling this product. Use of protective coveralls and long sleeves is recommended. **Respiratory Protection:** Use NIOSH approved respiratory protection. High airborne concentrations may necessitate the use of self-contained breathing apparatus (SCBA). **General:** Use good hygiene practices in handling this material. **Exposure Limits: (PARTS PER MILLION)**

Component(s)	TLV	OSHA-PEL	OSHA-STEL	SARA 313	Prop 65 VOC
None established					

Part 9: Physical & Chemical Properties

Solids: N/A PH: N/A Specific Gravity: 0.983 Physical State: Liquid %VOC: Approx. 0.0%

Evaporation Rate: Same as water Boiling Point: 212F Color: Off white Odor: Slight ammonia odor

Part 10: Stability & Reactivity

Hazardous polymerization will not occur. Condition to avoid: Keep away from sources of ignition. Avoid contact with strong oxidizers, reducers, acids, and alkalis. Stability: This product is stable under normal conditions.

Part 11: Toxicological Information

Polyalkylene glycol monobutyl ether: No relevant information found. **Nitrogen:** No data available.

Part 12: Ecological Information

No information available.

Part 13: Disposal Considerations

We make no guarantee of warranty of any kind that the use of and/or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Waste Disposal: Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations. Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes.

Part 14: Transportation Information

Ground Transportation: (Continental United States, Canada & Mexico): Consumer Commodity ORM-D

Ocean: UN 1950 Class 2.2 Aerosols, Limited Quantity

Air: We do NOT recommend this product to be shipped via air. It would need to be repacked by an authorized packing company and the DG would have to be completed by a licensed hazardous material shipping company.

Part 15: Regulatory Information

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30. CEPA-Domestic Substances List (DSL): All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

California Proposition 65

This product is not known to contain any of the components for which the State of California has found to cause cancer, birth defects or other reproductive harm.

Part 16: Other Information

H.M.I.S.

Health	1
Flammability	0
Reactivity	0
Special	-

The information in this MATERIAL SAFETY DATA SHEET is pursuant to 29 CFR 1910.1200 to convey information concerning the hazardous nature of this product. The information supplied was compiled from the most reliable sources available at the time of preparation and in light of the most reasonable foreseeable exposure situations expected from the intended use of this product. The material(s) may present greater or lesser hazard under other circumstances that are beyond the control of the manufacturer. Therefore it is imperative that all direction and warnings on the label be read and understood.