

## R2000 COOLING SYSTEM



### Specifications

- Factory set at 50 psi adjustable to 100 psi
  - 6 gallon reservoir (15 gallon available)
    - 115 VAC 50 / 60 Hz 1 ph
    - 230 VAC 50 / 60 Hz 1 ph
    - 13.4 / 6.7 amp:60 Hz 1 ph
  - 230 / 190 VAC 50 / 60 Hz 3 ph
  - 460 / 380 VAC 50/60 Hz 3 ph
    - 2.6 / 1.3 amp:60 Hz3 ph
    - 30,000 BTU
  - Dimensions: 23"L x 16"W x 19.5"H
- 1/4" FPT (water in / out) with 5/8" LH Standard Inert Gas Fitting
  - 8 foot power cord. 1 ph only
- Visible water level / water flow sight glass
  - Thermal overload
  - Net weight: 68 lbs/31 kg
  - Foam packed for UPS shipment

### R2000: Rotary GEAR Pump (only)

- 3.5 gpm at 50 psi
- Built in by-pass to tank
- Rebuildable Pump (Repair Kit Product No. P2001)

### System Features

- Stainless steel construction eliminates coolant contamination due to electrolysis or chemical reactions.
  - All units are plumbed with copper tubing and reinforced hose.
    - New extended life pump
  - No external plumbing is required because of closed loop water system.
- A water level float gauge and filler cap are combined in a single unit multi-purpose sight glass which enables operator to observe return water at a distance.
- Water filter on pump inlet protects pump and extends pump life.

Equipment	UPTO
M.I.G. guns	1000 amps
T.I.G. torches	1000 amps
PLASMA Welders / Cutters	300 amps
RESISTANCE Welders	150 KVA
INDUCTION Welding	10 KW

**SKU:** N/A | **Categories:** [Machines](#), [Water Recirculators](#) |



## GALLERY IMAGES



