

## R2000 COOLING SYSTEM



### Specifications

- Factory set at 50 psi adjustable to 100 psi
  - 6 gallon reservoir (15 gallon available)
    - 115 VAC 50 / 60 Hz 1 ph
    - 230 VAC 50 / 60 Hz 1 ph
    - 13.4 / 6.7 amp:60 Hz 1 ph
  - 230 / 190 VAC 50 / 60 Hz 3 ph
  - 460 / 380 VAC 50/60 Hz 3 ph
    - 2.6 / 1.3 amp:60 Hz3 ph
    - 30,000 BTU
  - Dimensions: 23"L x 16"W x 19.5"H
- 1/4" FPT (water in / out) with 5/8" LH Standard Inert Gas Fitting
  - 8 foot power cord. 1 ph only
- Visible water level / water flow sight glass
  - Thermal overload
  - Net weight: 68 lbs/31 kg
  - Foam packed for UPS shipment
- **R2000: Rotary GEAR Pump (only)**
  - 3.5 gpm at 50 psi
  - Built in by-pass to tank
- Rebuildable Pump (Repair Kit Product No. P2001)

### System Features

- Stainless steel construction eliminates coolant contamination due to electrolysis or chemical reactions.
  - All units are plumbed with copper tubing and reinforced hose.
  - New extended life pump
- No external plumbing is required because of closed loop water system.
- A water level float gauge and filler cap are combined in a single unit multi-purpose sight glass which enables operator to observe return water at a distance.
- Water filter on pump inlet protects pump and extends pump life.

| Equipment                | UP TO     |
|--------------------------|-----------|
| M.I.G. guns              | 1000 amps |
| T.I.G. torches           | 1000 amps |
| PLASMA Welders / Cutters | 300 amps  |
| RESISTANCE Welders       | 150 KVA   |
| INDUCTION Welding        | 10 KW     |

**SKU:** N/A | **Categories:** [Machines](#), [Water Recirculators](#) |



## GALLERY IMAGES



