

R4000 COOLING SYSTEM



Specifications

- Factory set at 50 psi adjustable to 100 psi
 - 25 gallon reservoir
 - 115 / 230 VAC 50 / 60 Hz 1 ph
 - 14.6 / 7.3 amp : 60 Hz 1 ph
 - 230 / 190 VAC 50 / 60 Hz 3 ph
 - 460 / 380 VAC 50 / 60 Hz 3 ph
 - 5.4 / 2.7 amp: 60 Hz 3 ph
 - 55,000 BTU
 - Dimensions: 36"L x 19.5"W x 35"H
 - 1/2" FPT SS Pipe - water in and out
- Visible water level / water flow sight glass
 - Net weight: 170 lbs / 77 kg

R4000: Rotary GEAR Pump (only)

- 10.0 gpm at 50 psi
- Built in by-pass to tank
- Rebuildable Pump (Repair Kit No. P4018)

System Features

- Stainless steel construction eliminates coolant contamination due to electrolysis or chemical reactions.
 - All units are plumbed with copper tubing and reinforced hose.
 - New extended life pump.
- Air flows into patented high efficiency radiator first for maximum efficiency.
 - No external plumbing is required because of closed loop water system.
- A water level float gauge and filler cap are combined in a single unit multi-purpose sight glass which enables operator to observe return water at a distance.

Equipment	UPTO
M.I.G. guns	1500 amps
T.I.G. torches	1500 amps
RESISTANCE Welders	300 KVA
INDUCTION Welding	15 KW

SKU: N/A | **Categories:** [Machines](#), [Water Recirculators](#) |



GALLERY IMAGES



