



Safety Data Sheet

Dynaflux SDS 305A 07/18/2018

Product: 305 SprayGalv Bright Finish (Aerosol)

Part 1: Product and Company Identification

Identification 305A

Trade Name: 305 SprayGalv Bright Finish (Aerosol)

Product Use: Sacrificial protection that stops rust and corrosion.

Manufacturers Name: Dynaflux, Inc.

241 Brown Farm Rd.

Cartersville, GA 30120 U.S.A.

Emergency Telephone Number: For U.S.: 800-255-3924 International: 813-248-0585

Part 2: Hazard(s) IdentificationSignal Word: **DANGER****H229:** Pressurized container: may burst if heated**H351:** Suspected of causing cancer**Warning:**

Contains gas under pressure. May explode if heated.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause damage to organs.

May be harmful if swallowed.

Part 3: Composition /Information on ingredients

		SARA III	PEL	TLV
Hazardous Ingredients	CAS No.	List	PPM	PPM
Dichloromethane	75-09-2	Yes	25	12.5
Propane	74-98-6	Yes	1000	1000
Zinc Dust & resin binder	7440-66-6	No	200	200
Aluminum flake	7429-90-5	Yes	15	10

Potential Acute Health Effects: Very hazardous in case of eye contact (irritant), of ingestion, of inhalation. Hazardous in case of skin contact (irritant, permeator). Inflammation of the eye is characterized by redness, watering and itching.

Part 4: First Aid Measures

Eye Contact: Flush with water for 15 minutes. If irritation persists call a physician. **GHS: Category 2A**

Skin Contact: Flush with water. Wash with soap and water. Apply a lotion. **GHS: Category 2**

Inhalation: Move to fresh air.

Ingestion: Do not induce vomiting. Give several large glasses of water. Seek medical attention. **GHS: Category 4**

Reproductive Toxicity: GHS Category 2

Carcinogenicity: GHS Category 2

Part 5: Fire Fighting Measures

Flashpoint: Nonflammable Flame Projection Test

U.E.L.: None Established

L.E.L. : None Established

Auto Ignition Temperature: 662°C.

Combustion Products: Carbon dioxide, carbon monoxide, hydrogen chloride and small amounts of phosgene.

Extinguishing Media: Foam, CO₂, Dry chemical

Unusual Fire and Explosion Hazard: use a self contained breathing apparatus. Use water fog to cool containers to prevent rupturing.

Part 6: Accidental Release Measures

Small Spill: Soak up with absorbent material, i.e. kitty litter, clay or dirt. Sweep up and place in a labeled closed container.

Large Spill: Keep unauthorized people from the area. Use self contained breathing apparatus. Dike area and pump contents to a labeled, closed container. Absorb residue and sweep up. Place in a closed, labeled container.

Part 7: Handling and Storage

Leave in the shipping containers. Store in a cool dry place. Do not expose aerosols to temperatures above 120° F or the container may rupture.

Part 8: Exposure Control / Personal Protection

If vapor exceeds TLV use a approved respirator. Use mechanical ventilation in confined spaces. Wear safety glasses and protective gloves.

Part 9: Physical and Chemical Properties

Boiling Point: NA

Vapor Pressure : 47.33 KPa

Vapor Density: NE

Appearance and Odor: Silver; chlorinated solvent odor

Evaporation Rate (BuAc=1): >1

Water Reactive: No

Part 10: Stability and Reactivity

Stability- Product is stable

Hazardous Polymerization- will not occur.

Conditions to Avoid- Ignition sources, open flames, amines and strong bases.

Part 11: Toxicological Information

Ingestion: Rat LD₅₀ 1500-2500mg/kg

Inhalation: Rat LC₅₀ 10,000 ppm

Carcinogenicity Classification: N.T.P. Anticipated Carcinogen. IARC: Possible carcinogen; 2B

Reproductive Toxicity: animal studies- None

Genetic Toxicity-negative results from animal studies.

Part 12: Ecological Information

Potential for mobility in soil is high.
Octanol/Water partition coefficient: 1.25
Organic carbon/water partition coefficient: 24
Atmospheric half life: 79-110 days
Biodegradation 5-26% 28 days
Aquatic Toxicity EC50 water flea. Immobilization: 480 mg/l

Part 13: Disposal Consideration

Do not dump into any sewers, on the ground or into any body of water. Send to a permitted recycler.

Part 14: Transportation Information**DOT HM-181 Shipping Information**

D.O.T. Shipping Name – Consumer Commodity
Hazard Class or Division: ORM-D
UN Number: 1950
Packing Group: III
Label(s) Required: None

TDG Shipping Information

TDG Shipping Name: Aerosols, Nonflammable
Hazard Class: 2.2
Sub classification : 6.1
UN Number: 1950
Packing Group: None
Label(s) Required: Non-flammable Gas

Part 15: Regulatory Information

Section 311 and 312
Immediate Health Hazard – Yes
Delayed Health Hazard- Yes
Fire Hazard – No
Reactive Hazard – No
Section 313- Dichloromethane
TSCA – The product on this MSDS, or all of its components, is listed under TSCA.
CEPA-(DSL) Listed

California Proposition 65 Statement:

WARNING: This product can expose you to chemicals including Dichloromethane, a chemical known to the State of California to cause cancer. For more information, go to www.p65Warnings.ca.gov/product.

Part 16: Other Information

Dynaflux, Inc.
241 Brown Farm Rd.
Cartersville, GA 30120 U.S.A.

Disclaimer of Expressed and implied Warranties:

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date of the Safety Data sheet was prepared. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices as specified on the label copy.